


Indexing plungers

Item description/product images



Description


Material:
Steel grade 5.8.

Version:
Trivalent blue passivated.

Note:
Indexing plungers are used to prevent any change in locking position due to lateral forces. A new locking position can only be set after the pin has been manually disengaged.

On request:
Special versions.

Drawings



Overview of items

Indexing plungers

Order No.	A	D	D1	D2	H	L	L1	L2	L3	SW1	Fx30°	Spring force initial pressure F1 approx. N	Spring force final pressure F2 approx. N	Tightening torque max. Nm
K0340.1104	16	4	M6	2,3	9,5	41,5	20	32	17	6	0,7	3	10	1,6
K0340.1905	19	5	M8	3	12	54	27	42	24	8	0,9	3,5	13,5	4,5
K0340.1206	23,5	6	M10	3,5	14	65	33,5	51	30	10	1,1	4	16	10

Indexing plungers

Overview of items

Order No.	A	D	D1	D2	H	L	L1	L2	L3	SW1	Fx30°	Spring force initial pressure F1 approx. N	Spring force final pressure F2 approx. N	Tightening torque max. Nm
K0340.1308	31	8	M12	4,7	19	73	31,8	54	28	12	1,3	4	22	13
K0340.1410	33	10	M16	4,7	25	102,5	50,5	77,5	44,5	16	1,6	4	23	42